

ATH Cross Lift® 40 UGA

Product Images



Description

- High-quality and robust hydraulic drive platform scissor lift with minimal maintenance requirements
- Powerful hydraulic unit with load-dependent lowering speed controller
- Suitable for pit installation
- With recesses for turning plates in the front and mechanically lockable sliding plates in the back, free-wheel lift (loading capacity: 4 t, lifting height: 450 mm), including rails for the optional rolling bridge jack, pluggable platforms-connections beams, incl. metal protections covers and switch for the optional 24V LED Lighting.
- Pneumatic unlocking of the safety locks, CE-Stop and acoustic signal through lowering
- Emergency lowering device for lowering in case of power failure, monitoring of safety synchronization by light barrier.
- Ideally suited for inspection, wheel alignment, repairing jobs and testing stations for driver assistance systems

Additional Information

Kolor	Anthrazit / czern
Udźwig	4.000 kg
Wysokość podnoszenia	2.160 mm
Długość platform	4.230 mm
Szerokość platform	600 mm
Moc napędowa	3,5 kW
Podnoszenie/obniżanie	ca. 70 s
Napięcie pracy	3x 400V / C16A
Fundament	min. C20/25 4.430 x 2.240 x 310 mm
Wysokość najazdu	295 mm

