

ATH W®64

Product Images



Description

- **Threaded shaft:** 40 mm clamping shaft for quick and secure wheel clamping
- **Sonar technology:** Non-contact rim width detection
- **Automatic positioning:** Automatically positions the wheel for weight attachment
- **Extended clamping shaft:** Additional clamping shaft for use with other clamping devices
- **Laser indicator:** Enables precise placement of the clamping weights at the 6 o'clock position
- **Static/Dynamic program:** Enables optimal balancing at different speeds
- **Alu balancing programs:** Special programs for aluminum rims to improve balancing quality
- **Split rear spoke weight positioning:** Enables precise weight distribution behind the spokes
- **Optimization program:** Program for fine-tuning and optimizing the balancing process
- **Optional motorcycle function:** Additional function for balancing motorcycle wheels

Additional Information

Średnica otworu środkowego felgi	45 – 130 mm
Czas pomiaru car truck	8 s
Tolerancja pomiaru	+/- 1g
Prędkość obrotów koła	200 U/min
Szerokość felgi	1,5" – 20"
Średnica felgi	10" – 24"
Max. średnica koła	900 mm
Max. waga koła	65 kg
Monitor	22" LCD
Moc napędowa	0,20 kW
Napięcie pracy	230V / C16A

