

ATH W®44 P Plus

Product Images



Short Description

ATH W®44 P Plus delivers accurate passenger car wheel balancing for professional workshops. The pneumatic 40 mm clamping shaft secures the wheel, while sonar technology measures rim width contact-free. Automatic positioning guides the wheel for fast and precise weight application, and a

laser indicates the exact placement point at the 5 o'clock position. Includes a clear LED display, wheel lifter, Speedplate Kit 5 and a large hood.

Description

- Pneumatic shaft: 40 mm clamping shaft for quick and secure wheel clamping
- Sonar technology: Non-contact rim width detection
- Automatic positioning: Automatically positions the wheel for weight attachment
- Extended clamping shaft: Additional clamping shaft for use with other clamping devices
- Laser indicator: Enables precise placement of the clamping weights at the 6 o'clock position
- Static/Dynamic program: Enables optimal balancing at different speeds
- Alu balancing programs: Special programs for aluminum rims to improve balancing quality
- Split rear spoke weight positioning: Enables precise weight distribution behind the spokes
- Optimization program: Program for fine-tuning and optimizing the balancing process
- Optional motorcycle function: Additional function for balancing motorcycle wheels

Including wheel lifter: ATH RRH1107

Including 5-finger speedplate kit

Including large clamping hood for aluminum rims

Scope of delivery:

- - Rim gauge
- - Weight pliers
- - 100g stop weight
- - Allen key
- - Mounting tool for balancing shaft
- - 4 cones 45 - 135 mm
- - Quick-release nut
- - Clamping cap
- - Balancing shaft

Additional Information

Średnica otworu środkowego felgi	45 – 130 mm
Czas pomiaru car truck	8 s
Tolerancja pomiaru	+/- 1g
Prędkość obrotów koła	200 U/min
Szerokość felgi	1,5" – 20"
Średnica felgi	10" – 24"
Max. średnica koła	900 mm
Max. waga koła	65 kg
Dopływ sprężonego powietrza	8 bar
Monitor	22" LED
Moc napędowa	0,20 kW
Napięcie pracy	230V / C16A

